

because now matters

VIGILANT S1500

Enterprise Flexibility in a Compact 1U Design





Every Now Micro solution comes equipped with DICE technology, offering OEMs and systems integrators a powerful suite of tools that streamlines deployment, reduces downtime with remote monitoring and simplifies asset management through a single, intuitive portal.







Intel® Xeon® E-Series processors for efficient performance



Up to 96TB of raw storage for compact deployments



1U rackmount form factor for space-efficient installations



Flexible RAID options with hardware RAID controller



5-year global next-business-day, on-site warranty









— **POWERED BY** — **DELL**Technologies

VIGILANT S1500

System

PROCESSOR

• Intel® Xeon® E-2434 Processor

OPERATING SYSTEM

- Windows Server IoT 2022 Standard
- Windows Server IoT 2019 Standard
- Windows 11 IoT Enterprise LTSC
- Windows 10 IoT Enterprise LTSC
- Windows Server 2022 Standard
- Windows 11 Professional
- Linux

MEMORY

- 16GB Standard, Supports Up to 128GB
- 4 x DDR5 DIMM slots

CAPACITY

Up to 96TB

RAID

• JBOD, 0, 1, 10

STORAGE CONTROLLERS

- · BOSS controller Card for OS Drive
- PERC H355 for Data Drives

GRAPHICS

· Matrox G200 16GB

GRAPHIC CARD OPTIONS

- NVIDIA RTX A400, 4GB, 4 x mDP
- NVIDIA RTX A1000, 8GB, 4 x mDP

I/O PORTS

Front:

- 1 x iDRAC Direct (MicroUSB)
- •1x USB 2.0

Rear:

- •1x USB 2.0
- •1 x USB 3.2 Gen1
- •1x VGA
- 2 x 1GbE RJ-45
- •1x Dedicated iDRAC Ethernet

NETWORKING

- 2 x Broadcom 5720 1GbE RJ-45
- •1x Dedicated iDRAC Ethernet Port

EXPANSION SLOTS

- 1 x PCIE x8 (x8 Electrical), Half Height (Open)
- 1 x PCIE x16 (x8 Electrical), Half Height (Open)

NIC OPTIONS

- 2 x 1GbE RJ-45
- 2 x 10GbE RJ-45
- 2 x 25GbE SFP28

HARDWARE MONITORING

- iDRAC Basic, Optional iDRAC Enterprise
- Now Micro DICE Enhancements Pre-Installed

WARRANTY

 5-Year Global Next-Business-Day, On-Site

Mechanical

FORM FACTOR

• 1U Rackmount

OS DRIVES

•1 x M.2 480GB

DATA DRIVES

 Up to 4x 3.5in Enterprise Class SATA Hot Swappable Drives

POWER SUPPLY

• Single Power Supply (1+0), 600w

MOUNTING

• Rail Kit Included

OPERATING TEMPERATURE

• 50°F to 95°F (10°C to 35°C)

OPERATING HUMIDITY

• Up to 80%, Non-Condensing

DIMENSIONS

- Height 1.685in (42.8mm)
- Width 18.976in (482mm) Includes Rack Ears
- Depth 20.178in (512.53mm) Not Including Bezel

