nowmicro

because now matters

STUDIO MPC2

Smooth 4K Playback in a Compact Design

The Studio MPC2 was made for reliable indoor digital signage, driving two 4K displays from a footprint small enough to tuck behind a screen. Its Intel® N150 Processor, SSD storage and active cooling deliver smooth, consistent playback for menu boards, lobbies and retail displays. Unlike consumer-grade mini PCs, it's backed by our warranty and support to keep your customer's screens up and running. Partner with Now Micro to reduce risk, save time, increase profits and maximize efficiency with purpose-built solutions that are backed by people who care and powered by innovation.

KEY FEATURES

- Ultra-small design
- Dual 4K HDMI outputs
- Intel® N150 Processor
- Wireless networking
- 3-year depot warranty

dice

powered by nowmicro

Now Micro solutions come ready to integrate with DICE technology, offering integrators and OEMs a powerful platform that streamlines deployment, reduces downtime with remote monitoring and simplifies device management through a single, intuitive portal.

- Remote Desktop
- Order Tracking
- Support Ticket Management
- API Integration
- Device & Organization Management
- Real-Time Device Health
- Backup & Recovery
- Automated Deployment & Updates

intel INSIDE

HDMI™ HIGH-DEFINITION MULTIMEDIA INTERFACE

nowmicro.com | nowmicro@trafera.com | 651.393.2100

STUDIO MPC2

System

PROCESSOR
- Intel® N150 Processor

OPERATING SYSTEM
- Windows 11 IoT Enterprise LTSC
- Windows 10 IoT Enterprise LTSC
- Windows 11 Professiona l
- Linux

MEMORY
- 8GB

STORAGE CONTROLLERS
- Intel® Integrated SOC

GRAPHICS
- Intel® UHD Graphics

I/O PORTS
Front:
- 2 x USB 3.0
- 1 x USB 3.2 Type C
- 1 x 3.5mm Audio Out

Rear:
- 2 x HDMI 2.0
- 2 x USB 2.0
- 1 x 1GbE RJ-45

NETWORKING
- Realtek RT8111H 1GbE RJ-45
- Wireless

SECURITY MODULE
- Intel® Platform Trust Technology

WARRANTY
- 3-Year Depot

Mechanical

FORM FACTOR
- Ultra Small Form Factor (USFF) Fanless Operation

OS DRIVES
- 128GB SSD

POWER SUPPLY
- 30W AC Adapter

MOUNTING
- Mounting bracket included

OPERATING TEMPERATURE
- 32°F to 104°F (0°C to 40°C)

OPERATING HUMIDITY
- Up to 90%, Non-Condensing

DIMENSIONS
- Width – 4.7in (120mm)
- Depth – 4.3in (110mm)
- Height – 1.3in (33mm)

nowmicro

© 2026 Now Micro. All rights reserved.
Specifications subject to change.
10.26